

FIG. 1
(Prior Art)




FIG. 2




FIG. 3




FIG. 4
(Prior Art)

#

Interframe Fill 0111 1110	Address 1 or 2 bytes	Control 1 or 2 bytes	Data 0 to X bytes	Checksum (FCS) 1 or 2 bytes	Interframe Fill 0111 1110
---------------------------------	-------------------------	-------------------------	----------------------	-----------------------------------	---------------------------------

Basic HDLC frame format

Flag 0111 1110	Address 1111 1111	Control 0000 0011	Protocol ID 1 or 2 bytes	Information Variable/Pad	FCS 2 or 4 bytes	Flag 0111 1110
-------------------	----------------------	----------------------	--------------------------------	-----------------------------	---------------------	-------------------

Basic PPP frame format

FIG. 5
(Prior Art)




FIG. 6(a)
(Prior Art)

REQUEST

0000	No Request
0001	Do Not Revert (nonrevertive only)
0010	Reverse Request (bidirectional only)
0100	Exercise
0110	Wait-To-Restore (revertive only)
1000	Manual Switch
1010	Signal Degrade
1100	Signal Fail
1100	Forced Switch
1111	Lockout of Protection

FIG. 6(b)
(Prior Art)

MODE / INDICATION

100	Provisioned for Unidirectional Switching Mode
101	Provisioned for Bidirectional Switching Mode
110	Line Remote Defect Indication (RDI-L)
111	Line Alarm Indication Signal (AIS-L)

FIG. 6(c)
(Prior Art)




FIG. 7